


EU Declaration of Conformity

Product:		Guard Locking Solenoid Safety Switches
Name and address of the manufacturer:		Name and address of the authorised representative:
Rockwell Automation Inc. 1201 South 2nd Street Milwaukee, WI 53204 U.S.A.		Rockwell Automation NV Pegasus Park De Kleetlaan 12A 1831 Diegem Belgium
This declaration of conformity is issued under the sole responsibility of the manufacturer.		
Object of the declaration:		Allen-Bradley 440G-MT Series (reference the attached list of catalogue numbers)
The object of the declaration described above is in conformity with the relevant Union harmonisation legislation:		
2006/42/EC	Machinery Directive	(MD)
2011/65/EU	RoHS Directive	(RoHS)
References to the relevant harmonised standards used or references to the other technical specifications in relation to which conformity is declared:		
EN ISO 14119:2013	Safety of machinery – Interlocking devices associated with guards – Principles for design and selection	
EN IEC 63000:2018	Technical documentation for the assessment of electrical and electronic products with respect to the restriction of hazardous substances	
Additional information:		
Person authorised to compile the technical file (MD):	Authorised representative (see details above).	
Product Safety Function (MD):	Type 2 interlocking devices per EN ISO 14119.	
Signed for and on behalf of the above named manufacturer:		
Place and date of issue:	Milwaukee, WI U.S.A.	11-Jun-2021
Name, function:	Daniel L. Nachtigall, Technical Leader – Product Compliance Engineering	
Signature:		

<i>Catalogue number ¹</i>	<i>Series ²</i>	<i>Description</i>
440G-MT47***		<i>Guard locking safety switch w/3 N.C. safety contacts + 1 N.O. auxiliary contact or 2 N.C. safety contacts + 2 N.O. auxiliary contacts</i>
440G-M3NBGDH-AC		<i>Guard locking safety switch w/3 N.C. break-before-make (BBM) safety contacts, GD2 standard actuator, M12 QD cordset</i>
440G-M3NBBDH-AC		<i>Guard locking safety switch w/3 N.C. break-before-make (BBM) safety contacts, alignment guide and flexible actuator, M12 QD cordset</i>

- 1) * Denote suffix numbers defining specific characteristics related to solenoid voltages between 24...230V AC/DC, safety/auxiliary contact type and configuration, actuator type, and connection type.
- 2) Products of the series level indicated, as well as succeeding series levels, are certified. If no series letter or number is given, then all series are certified.